



HAL
open science

METSTOR: A GIS to look for potential CO₂ storage zones in France

Didier Bonijoly, Minh Ha-Duong, Aurélien Leynet, Alain Bonneville, Daniel Broseta, Aude Fradet, Yann Le Gallo, Gilles Munier, B. Nédelec, Vincent Lagneau

► **To cite this version:**

Didier Bonijoly, Minh Ha-Duong, Aurélien Leynet, Alain Bonneville, Daniel Broseta, et al.. METSTOR: A GIS to look for potential CO₂ storage zones in France. Greenhouse Gas Control Technologies 9, Proceedings of the 9th International Conference on Greenhouse Gas Control Technologies (GHGT-9), Nov 2008, Washington, United States. pp.2809-2816, 10.1016/j.egypro.2009.02.053 . halshs-00451712

HAL Id: halshs-00451712

<https://shs.hal.science/halshs-00451712>

Submitted on 2 Feb 2010

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

METSTOR: a GIS to look for potential storage zones in France

D. Bonijoly¹, M. Ha-Duong⁶, A. Leynet¹¹; A. Bonneville², D. Broseta³, A. Fradet⁵, Y. Le Gallo⁴,
G. Munier⁷, B. Nédelec⁸, and V. Lagneau⁹
with contributions from: A.-L. Auzende², J. Berthiaud⁵, A. Bialkowski¹, D. Bossie-Codréanu⁴, E.
Brosse⁴, G. Bureau⁵, A.-S. Campos⁶, S. Fillacier⁷, C. Lagny⁸, Z. Pokryszka⁸, D. Rambourg¹, C.
Rigollet^{1,5}, P. Roux⁸ and S. Saisset⁵

¹BRGM, 39-43, quai André Citroën – 75739 Paris cedex 15, France;

²IPGP, Institut de Physique du globe de Paris, 4 place Jussieu, 75252 Paris cedex 05, France;

³Université de Pau, av. de l'université – BP 576 – 64012 Pau cedex, France;

⁴IFP, 1 & 4 Avenue de Bois-Préau – 92852 Reuil-Malmaison cedex, France;

⁵Gaz de France, 23, rue Philibert Delorme, 75017 Paris, France;

⁶Cired, Campus du J. Tropical, 45 bis av. de la belle Gabrielle, 94736 Nogent-sur-Marne, France;

⁷Géostock, 7 rue E. et Armand Peugeot 92563 Reuil-Malmaison cedex, France;

⁸Inéris, Technologique Alata, BP 2, 60550 Verneuil-en-Halatte, France;

⁹ENSMP, 60-62, Boulevard Saint-Michel 75272 Paris cedex 06, France;

Abstract: The METSTOR project offers a methodology to look for potentially interesting CO₂ storage areas in France at the initial stage, before the “site selection” step. That methodology is embodied in a Geographic Information System (GIS). In addition to storage capacities, relevant information layers such as seismic risk, presence of faults, protected natural areas, existing wells, population density and other vulnerability factors will be included. Our tool is based on an interactive map of CO₂ storage capacities. It describes ‘effective capacities’ (according to the Carbon Sequestration Leadership Forum standards) in both the Triassic and Dogger aquifers, depleted fields, and ‘theoretical capacities’ in some unexploited coal deposits. Consideration of all the technical, social and environmental aspects of storage led us to complement the geographic layers with a series of online technical notices, because many aspects can not be mapped meaningfully. These notices include, for example, methods for both short-term and long-term risk assessments, descriptions of gas transport and injection technical solutions, methods to analyze acceptability. To the best of our knowledge the METSTOR prototype is the first open online GIS that offers policy makers, businesses and the public at large an integrated access to that necessary information. Our prototype based on pre-existing data and limited mainly to the Paris Basin is to be released online at www.metstor.fr.

¹ Corresponding author. Tel.: +33 2 38 64 38 90; fax: +33 2 38 64 36 85. *E-mail address:* a.leynet@brgm.fr.

Keywords: CO₂ storage; carbone capture and storage; Methodology; France; site selection; Geographic Information System; storage capacities; aquifers; coal deposits; depleted fields; risk assessment

1. Introduction

1.1. Project background

The METSTOR project was implemented by the BRGM, IFP, Inéris, Gaz de France, Géostock, Cired, University of Pau and IPGP under the auspices of the Ademe in the 2006–2008 period. The aim of the project was to design a decision-making tool for initial selection of sites for geological storage of carbon dioxide (CO₂). Once successfully completed the project would provide information to industrial concerns interested in reducing their greenhouse gas (GHG) emissions and also inform the general public about the potential of techniques for capture and geological storage of CO₂.

A website (www.metstor.fr) has been created to support this aim, providing those interested with clear, simple and accurate information on the various themes surrounding capture and geological storage of CO₂. This is seconded by an interactive mapping engine that allows users to appropriate a methodology via a tool for assessment of geological storage capacities in a given area.

The global approach underlying the project led to a search for exhaustiveness in the results delivered to users: information is given on potential storage formations (aquifers, hydrocarbon deposits, coal beds, basic and ultrabasic rocks); on risks (seismic risk, environmental vulnerability, abandoned shafts, etc.); and on associated socio-economic issues (land use, nature reserves, etc.).


However, as for any project, the aim of METSTOR is not to deliver a merely publishable outcome but, via the creation of a demonstrator model, to evaluate the concept and identify and remove any possible obstacles so as to, ultimately, deliver a fully finished product able to give sufficiently accurate information for the complete mapping of storage capacities throughout metropolitan France.

1.2. System use scenarios

Take an industrial plant in the city of Orléans (France) that is emitting CO₂. The management wishes to assess the feasibility of geological storage in the environs.

The mapper will show two potential CO₂ storage reservoirs, and it can be seen that there are two possible formations: the Dogger (in blue) and Trias (mauve) aquifers in the Paris region. The orange circle traced out by the user (with a radius that must be between 20 and 100 km) underpins the estimations.

Figure 1: Screenshots from METSTOR (08/2009)



The report includes:

- cartographic information describing the study area;
- sources of CO₂ emissions greater than 100 kt/yr, with as many as 15 parameters per source;
- the geological storage capacities: the effective capacities of the Dogger and Trias aquifers, the effective capacities of the hydrocarbon reservoirs and the theoretical capacities of the coal deposits;
- additional useful information: existing wells, faults, oil extraction areas, protected areas, etc.;

For example, an effective capacity of around 2 000 Mt can be deduced within the 40 km radius considered, entirely in the aquifers.

The GIS can also show additional information such as major faults (black lines) and oil extraction areas (grey areas).

1.3. GIS and technological projects affecting the environment

Communication instruments on CO₂ capture and storage often address the issue from a marketing point of view, i.e. with the intention of augmenting acceptability which is viewed as malleable and exploitable. The underlying assumption is that, since engineers are able to control all of the risks, effective communication is all that is necessary. The METSTOR approach is different, recognising that full and free access to information is now the norm.

There is widespread agreement in the scientific literature that one of the main factors influencing risk perception is the use of forms of planning that, as a necessity, include consultation ahead of the actual spatial planning phase and which

do not therefore simply decide, announce and (possibly) gain acceptance in public opinion. In the public mind, citizens are able only to make judgements about the decision-making process, as they are not specialists in risk assessment. If the way in which policy is made is accepted and shared, then the technology will eventually become firmly rooted.

The Aarhus Convention, in force for some years now, makes provision of access to information and the possibility of public participation in environmental matters mandatory. An essential point is that participation is to take place when options and solutions are still open and the public can exert an effective influence, that is to say upstream of projects: a project proposed for discussion must be genuinely reversible and public participation must allow the choice between several possibilities as well as discussion of the very advisability of a project.

The public must, within reasonable timeframes, be provided with knowledge of the different procedural stages and must have access to all relevant information needed to understand the implications of decisions 'freely and as soon as it becomes available'. In this regard, European Directive 2003/4/EC, which enacts the Convention, stipulates that all local authorities must provide all environmental information they possess to anyone requesting it (without the need for any proof of identity nor justification for the request).

METSTOR meets these requirements fully. It is a complement to modern consultation instruments that express technological development projects in terms of public policy rather than in terms of technical aspects that can be resolved via concepts such as energy, efficiency or probability.

The METSTOR GIS can be used by all of the stakeholders concerned by storage of CO₂ to give substance to discussions that go beyond the simple NIMBY effect to become mechanisms and channels for expression of different forms of support or opposition, usually conditional. The interlinkages and implications that arise from a geological CO₂ storage project include: reformulation of the relationship between environmental and economic or industrial issues, regional planning, land use, etc.

METSTOR does not therefore contain acceptability maps. Local acceptability of industrial projects is generally conditional (i.e. subject to different expectations) and usually varies between different social sub-groups. Its determinants include both historical trajectories and human factors (confidence, competence and perceived fairness, etc.). There is, therefore, no sensible ex ante reason for presenting a map of a variable such as potential acceptability of CO₂ storage. The available international literature does not include geographical factors in explaining opinions about the technology, as confirmed by analysis of the data obtained from a survey of the French population as part of the METSTOR project. The idea of an

acceptability map makes sense not as the product of a GIS inter-relating statistical, technical and administrative factors, but as a product of public policy.

For similar reasons, an approach based on optimisation is not justifiable for METSTOR. In a multi-stakeholder, multi-criteria decision-making context where uncertainty is high the idea of an ‘a priori best site’ is groundless. Site selection is seen more as the result of a process of participation than as an optimisable technological variable. The maps METSTOR provides can merely support co-construction of local development projects.

2. Capacity calculation methods

2.1. Definitions of capacity from the Carbon Sequestration Leadership Forum

In practice, the capacity of a reservoir for geological storage of CO₂ is difficult to evaluate, but different levels of approximation have, nonetheless, been established. These values depend on numerous physical, geological and even economic parameters that are themselves often difficult to evaluate.

To prevail itself of a globally recognised standard, the METSTOR project relies on the considerations and approaches defined by the group of international experts of the Carbon Sequestration Leadership Forum (CSLF).

The CSLF distinguishes four types of storage in descending order of volume:

- Capacities referred to as ‘theoretical’ which comprise the entire porous volume accessible to CO₂, fluid saturation and maximum adsorption in coal.
- ‘Effective’ or ‘realistic’ capacities, supposing realistic reservoir behaviour: these capacities therefore include technical characteristics such as saturation in water, fracturing of rock, heterogeneity, etc. They vary widely as new data and new knowledge are acquired.
- ‘Practical’ capacities integrate the socio-economic and regulatory constraints on storage. They may therefore evolve rapidly with technology, policies or economic conditions. Practical storage capacity corresponds to the ‘reserves’ of the energy and mining industries.
- ‘Matched’ capacities, which are those resulting from actual geological storage projects, when all parameters have been taken into account.

In METSTOR, the definitions used are those of theoretical and effective capacities. At present it is not possible to refine (practical) capacity calculations for an entire basin.

The partners in the METSTOR project have calculated effective geological storage capacities of CO₂ for the Dogger and Trias oil fields in the Paris basin, using operational data. Given that some of these data are not publicly available we have had to mask the calculation values as well as, for example, the exact extent of the fields.

2.2. Effective aquifer reservoir capacities

Deep saline aquifers at depths beyond 800 m constitute one of the solutions for geological storage of CO₂. These are porous and permeable geological formations at great depth that contain hypersaline water. Impermeable layers (clay, marls and salt) cap and underlie these deep aquifers forming a sealing barrier.

The METSTOR project investigated the geological CO₂ storage capacities of the deep saline aquifers in the Paris basin. Two target reservoirs, Dogger and Keuper, were examined. Their wide geographical extent at depths of between 800 and 1000 m, their position immediately below points of CO₂ emissions and the existence of impermeable covering layers guaranteeing sequestration made them places of choice for future injection and storage facilities.

The formulae recommended by the CSLF served as the basis for assessment of capacities (theoretical and effective). Irreducible water saturation was considered as constant for each aquifer: 20 per cent for Dogger and 30 per cent for the Trias. Porosity was defined in accordance with the schematic maps. Porosity varies within the Dogger aquifer through values of 0, 3, 6 and 12 per cent; 6, 7, 12 and 18 per cent in the Trias.

Effective capacity is deduced from the theoretical capacity by applying a capacity coefficient C_c . To evaluate the capacity coefficient, an equivalent calculated from available data on the hydrocarbon deposits in the Paris basin was used. C_c is approximated from the average over the Paris basin oil fields of the ratio of the volume of oil produced to the porous volume. The calculations give a capacity coefficient of 2.15 per cent for Dogger, 3.7 per cent for Keuper.

Finally, and allowing for some imprecision in the model, the effective geological storage capacities in the Paris basin are estimated at 13.6 gigatonnes (Gt) for Dogger and 15.5 Gt for Keuper. These figures are to be compared with those given under the GESTCO programme which assessed the theoretical capacities of the Paris basin Dogger at 4.3 Gt and at 176 Gt for Keuper. Although going from theoretical to effective capacities normally results in a reduction in the capacities as a result of the integration of more accurate data, it nonetheless appears that the restrictions applied under GESTCO were too severe.

2.3. Theoretical capacities of coal beds

Over and above its characteristics as an energy source, coal forms a heterogeneous and microporous environment characterised by a very great specific surface. This property gives it a high theoretical potential for gas storage. Coal can store gases in several ways:

- Adsorption at the inner surface: this the form of capture that a priori involves the greatest volume;
- Adsorption in the coal's molecular structure;
- As free gas in the voids;
- In solution in the deposit water.

CO₂ is adsorbed by coal in preference to methane (CH₄). There is therefore a possibility, in theory, of recovering and using the methane, offering a possible economic advantage.

Calculation was proposed and performed in the METSTOR project for a site in the Gardanne basin. The chosen level of accuracy of capacity was the theoretical capacity: total saturation of coal in terms of both porosity and adsorption. A more accurate study of the capacity will have to incorporate well distribution, the pressure field, anisotropy, heterogeneity, permeability, etc. The formula used to estimate the theoretical CO₂ storage capacity is that specified by the CSLF.

The formula applies to conditions of storage of CO₂ in the gaseous state. The mineral fraction of the coal (ash) is considered to be inert to CO₂. The adsorption capacity is determined from Langmuir theory. The formula states that the quantity of gas adsorbed at increasing pressure P tends towards a finite limit corresponding to saturation at all of the adsorption sites of the coal's inner structure. In practice, adsorption capacities depend on several other factors such as: the intrinsic characteristics of the coal, temperature, humidity, ash content, gas composition, etc. Similarly, several configurations are possible, depending on whether the coal bed originally contains gas or not (most often CH₄ and CO₂), and whether or not this gas is recovered prior to storage (as is the case for methane).

Prior to CO₂ storage, in-depth experimental studies should be conducted in coal from the target bed in order to determine the characteristics of the main seams and estimate the bed's storage capacity in the light of the various parameters and configurations presented above.

2.4. Basic and ultrabasic formations

Basic and ultrabasic rock formations—such as basalts, peridotites or serpentinites (hydrated peridotites)—are to be included in the formations usually considered as

potential reservoirs for geological storage of CO₂. These formations are very common throughout the world, and some of them are close to sources of CO₂ emissions. The principal form of storage in these rocks is mineral sequestration (precipitation of carbonate or mineral carbonation), which has the advantage of high security over considerable periods.

Carbonation is obtained by weathering of rocks through the simple mineral reaction represented below:

$M\text{SiO}_3 + \text{CO}_2 \rightleftharpoons M\text{CO}_3 + \text{SiO}_2$, where M is the divalent cation. This type of equation can be written for any mineral pole containing (Mg²⁺, Fe²⁺, Ca²⁺, Na⁺, etc).

Since the Precambrian period (Massif armoricain, 620 Ma), France has experienced numerous magmatic and volcanic episodes that have produced basic rocks. The Massif Central is the area of territory where magmatism was most active and the most recent, and is where the most widespread outcropping volcanic terrain is found. The total area of continental France's territory covered by basic and ultrabasic formations is estimated to be 9 306 km², i.e. 11.7 per cent of the country. The northern tip of Corsica also comprises basic and ultrabasic areas (ophiolites, serpentinites, etc.) favourable for CO₂ storage.

In overseas territories, New Caledonia has wide expanses of ultrabasic rocks (peridotites, serpentinites, etc.) covering around one-third of the emerged territory (5500 km² of Grande Terre), the Grand Massif du Sud being one of the world's largest ultrabasic massifs. Moreover, intensive mineral exploration in these massifs has resulted in waste piles of these ultrabasic rocks that can be used for ex situ CO₂ carbonation. And lastly, Reunion Island, consisting entirely of basaltic rocks, could provide large *in situ* storage capacities.

A lack of petro-physical or geophysical data on these formations makes estimation of the actual CO₂ storage capacities difficult at present.

3. Other factors mapped

The GIS allows the storage capacities to be viewed against numerous other relevant factors for initial site selection. To ensure this, simple access to a number of general references is provided via:

- Land use, from the Corine Land Cover 2000 database (IFEN); <http://www.ifen.fr/bases-de-donnees/occupation-du-sol.html>
- Topography of metropolitan France (GEOSIGNAL base); <http://www.geosignal.fr/>
- Water courses (SANDRE basis); <http://sandre.eaufrance.fr/>

- Geological map of France (BRGM); <http://infoterre.brgm.fr/>
- Subsurface database (BRGM's BSS base). <http://infoterre.brgm.fr/>

The system allows users to superimpose their own layers hosted on a WMS (OGC) server. It also takes specific account of three additional factors. First, CO₂ sources in France have been mapped. Second, certain vulnerability factors can be represented: in particular, population density; protected areas; and a vulnerability index for the different environments. Third, maps of risk factors and recommendations for preliminary risk analysis are included.

3.1. Mapping of CO₂ sources in France

METSTOR GIS provides access to a localised inventory of the principal sources of CO₂ emissions in France. This geography of France's CO₂ emissions primarily covers units emitting at least 1 Mt of CO₂ per year. It is neither an official nor an exhaustive record. The database constructed gives the geographical position of the emitter, the type of industry in question, the volume of CO₂ emitted annually and, in so far as possible, the composition of the gas emitted and its pressure. These data are obtained from three public databases: iREP, ULCOS and GESTCO.

iREP: Le Registre français des Émissions Polluantes (France's polluting emission register) (<http://www.pollutionsindustrielles.ecologie.gouv.fr/IREP>), into which operators' annual declarations are fed, meets the requirements of European Directive 96/61/EC on integrated pollution prevention and control (the 'IPPC' Directive). It is managed by the Pollution and Risk Prevention Department of the Ministry for Ecology and Sustainable Development, supported by the International Office for Water. The facilities covered are environmentally 'classified' facilities subject to a requirement for prefectural authorisation, and more particularly those covered by the IPPC Directive. The register covers 100 pollutants for emissions to water, 50 for emissions to the air and 400 categories of hazardous waste.

The European Pollutant Emission Register (EPER–EU) (<http://eper.eea.europa.eu/>) is the first pan-European register of industrial emissions to the atmosphere and to water. It was created by a Commission Decision of 17 July 2000. Under the EPER decision, Member States must produce a report every three years on emissions from industrial facilities into the atmosphere and into water (9 200 facilities in 2001, 12 000 in 2004). The reports cover 50 pollutants and, in practice, 90 per cent of emissions from the listed facilities are covered. In 2007, the EPER was replaced by the European Pollutant Release and Transfer Register (E–PRTR). The information this contains relates to: pollutants, activities and emissions to the air or to water (either direct or via the sewerage system).

GESTCO is an FP 5 project intended to assess the potential and technical-economic feasibility of sequestration of CO₂ in deep aquifers, depleted oil and gas fields or deep coal seams. In this context, BRGM has made an inventory of the major industrial sources of CO₂ emissions in France, compiled from different data sources: the Centre Interprofessionnel Technique d'Études sur la Pollution Atmosphérique (CITEPA – inter-professional centre for technical study of atmospheric pollution), the Ministry for Industry and a Europe-wide inventory made by the Dutch company ECOFYS. CITEPA and ECOFYS have made an estimate of CO₂ emissions per facility via annual production weighted by an emissions factor per type of production and annual duration of activity of the facilities.

3.2. Mapping of vulnerability factors

There are three aspects to vulnerability to risks arising from geological CO₂ storage: material, environmental and human. The common denominator allowing representation is the density of the targets.

METSTOR GIS provides a view of population density as recorded by the INSEE (France's national statistics office), which appears as the initial vulnerability factor. Below, by way of example, are the recommendations of a panel of citizens, interviewed in 2008 (EPE survey), on living in a CO₂ storage zone. Panel members declared that they were willing to live in a CO₂ storage zone but nevertheless stressed the following conditions to reassure the population:

1. Information and awareness raising for the population as to the advantages of CO₂ storage (even though support of the population is not necessarily required).
2. Consultative approach via local commissions involving the population, public interest inquiries by appointed investigating inquirers.
3. Networking of cities concerned by CO₂ storage, with a view to sharing experiences with other cities.
4. Training for the population on management of health risks.
5. Close monitoring of the CO₂ storage site: installation of sensors, etc.
6. Population evacuation plan in case of problem, even minor.
7. The panel, nonetheless, recommended choosing places with low population density.

In a more refined study, other factors of human vulnerability would have to be considered. The locations and capacities of buildings in which members of the public congregate, such as schools or retirement homes, as well as communications infrastructure are generally considered in industrial risk studies.

For environmental vulnerability, METSTOR GIS shows two types of information: protected areas and a summary vulnerability index based on land use. The network of protected areas in France involves a variety of tools and instruments each with its own aims, constraints and (more or less constraining) management modes:

- Regional natural parks and agro-environmental measures come under a contractual local approach to protection and management. Development of economic activities is not generally excluded from these areas, with local stakeholders taking a stance that attempts to reconcile development and conservation.
- National parks and nature reserves come under a regulatory protective approach. These areas aim for long-term protection of heritage. The approach is closer to exclusion of human activities than to development.
- The Natura 2000 network is made up of special protection areas (SPA) under the 'Birds' directive and special conservation areas (SCA) under the 'Habitats' directive. These instruments provide protection at the European level; management is contractual and voluntary. Projects likely to significantly affect natural habitats and species on a Natura 2000 site must be subject to impact assessment. Public authorities may intervene to regulate access to certain areas or the practice of certain activities, especially industrial, in cases of overriding public interest, including economic interest.

The summary vulnerability index is based on land use. The geographical data employed use the European reference in the area of biophysical land use, the CORINE Land Cover (CLC) database, created, maintained and distributed by the Institut Français de l'Environnement (IFEN – France's institute for environment).

The formula for calculation of the index is adapted from the method developed by J. Tixier as part of the ARAMIS project. For each element of a 500 m square grid the sum is calculated of the areas of each of the four main categories of land cover listed in Table 1, weighted by relative vulnerabilities. Weightings are extracted from the ARAMIS expert survey of relative vulnerability of different environments, assuming a risk from CO₂ relating only to its toxicity and liquid pollution.

Table 1: environmental vulnerability indices per land use category (Source: ARAMIS expert survey)

Land cover (1st level CLC category)	Weighting
Agricultural areas	0.242
Forests and semi-natural areas	0.136
Protected wilderness	0.255
Wetlands and water bodies	0.367

The material vulnerability factors are the other economic activities that may be impacted by CO₂ storage. Some ‘Seveso’ facilities may also impose constraints that need to be considered. The prevention policy for major industrial accidents in France sets high standards in controlling risk at source, response planning, control of urbanisation around risk sites, and provision of information to populations. Even if CO₂ storage has its own regulatory framework, these standards provide a reference for the levels of expectation of local communities.

3.3. Help sheets for initial risk analysis

METSTOR contributes to initial risk analysis in two ways. First, the system allows mapping of certain natural risk factors and then, going further, proposes a set of method sheets. Displayable risk factors relate to:

- Swelling and shrinkage of clays (MEEDDAT/BRGM) (<http://www.argiles.fr/>)
- Major faults in metropolitan France (BRGM)(<http://www.planseisme.fr/>)
- Seismic zoning (MEEDDAT /BRGM) (<http://www.sisfrance.net/>)
- Existing wells in Dogger and Trias (BRGM) (<http://www.infoterre.brgm.fr/>)

Where method is concerned, each geological storage project is unique and it is up to the decision-maker to conduct a risk assessment suited to the context for all of the activities relating to implementation of storage within the framework of a global risk control approach. Implementation involves both the activities in stationary facilities and those of transport. For each storage process associated with a manufacturing or stock management process, it will allow identification of a risk criterion representative of each underground storage process that will influence the decision-maker's decision.

The links in the CO₂ transport and storage chain within the scope of the METSTOR project are as follows:

- terrestrial pipelines from place of capture to place of underground storage without recompression or pressure reduction stations;

- stationary pressure regulation facilities (relief valve or recompression pump) upstream of wellhead;
- surface and underground injection facilities (wellhead, wells);
- CO₂ storage deep underground in geological formations: saline aquifers, exhausted oil and gas fields, unexploited coal beds and basic rocks.

Feedback on accidents involving CO₂ indicate two major types of accident that can be caused by the gas:

- First, leaks that have had toxic effects for humans, mainly releases in confined spaces.
- Second, explosions of emissions from vessels containing CO₂ in either gaseous or pressurised liquid forms. In the first instance, these are classic bursting of storage vessels. In the second, the term 'BLEVE' applies.

Leaks may occur in transport or at well injection facilities as a result of equipment failures or inflicted damage or destruction. Bursting of transport pipes with ensuing leaks cannot be discounted.

Moreover, even if one of the main criteria for choice of potential storage sites is low permeability of the capping layers, some migration of the gas towards the surface cannot be excluded.

Where geological storage of CO₂ is concerned, it is therefore important to identify and assess the risks and to then select from amongst them the most important for the physical and human environment of the storage facility, so as to map them.

Risk is defined as a combination of the probability (or frequency) of occurrence of a hazardous phenomenon, its intensity and the vulnerability of the area exposed to it. Estimating probability involves identifying initiating events, the causes of hazardous phenomena, and of estimating their frequency. It also involves identification and qualification of safety barriers which counter the progress of an accident scenario from the initiating event through to the hazardous phenomenon.

A methodology for risk analysis suited to the context of the METSTOR project has been developed. The main stages relate to identification of:

- technological risks of terrestrial pipeline transport and injection of CO₂ (short-term risk);
- risks relating to leaking of gas from the place of geological storage to the ground surface, via the capping material and shallower aquifers (short- and long-term risks).

Risk assessment is the stage beyond risk analysis. It consists in deciding whether the risks identified are acceptable or are adequately controlled. This stage is not

carried out formally in the METSTOR project, work being limited to an initial risk analysis provided to users in the form of information sheets.

4. Conclusion

The procedures developed for METSTOR, mainly in the Paris basin, prefigure a national map of estimated capacities for geological storage of CO₂. New data should become available from research in progress in the south-east of the basin. Interest could then switch to the Aquitaine basin and the Lorraine coal basin, the basic and ultrabasic rocks of New Caledonia or to other aquifers in the Paris basin.

The procedures for assessment of storage capacities could be refined technically. Better definition of the geological parameters—e.g. density of super-critical CO₂ (depending on temperature and pressure)—or more precise capacity coefficients per aquifer (C_c) would make capacity estimates more accurate.

The process of improvement introduced to meet users' expectations and needs includes several actions. Content of texts used must be updated to keep pace with developments in national, European and international practice, and a regular current-information roundup should be organised. A moderated forum would allow users to put forward their points of view and to address questions to experts. Analysis of connections statistics allows for monitoring of actual use: requests leading to the site, points of entry and visitors route around the site, pages viewed most frequently, geographical and institutional characteristics of visitor's IP address. An attempt will also be made to assess the impact of the tool on public debate, via a media scan and through direct dialogue with the stakeholders in an actual geological CO₂ storage project.